



RACK MOUNTED/USER CONFIGURABLE POWER AND DATA DISTRIBUTION HUB

- 1 Single 125V AC, 5A max, NEMA 5-15 accessory outlet. 125V AC 60 Hz in through back mounted IEC, C14 male inlet. With user replaceable 3 foot cord.
- 2 Over load circuit protection by 5A thermal circuit breaker. Resettable at front panel.
- 3 2x powered USB for smart phones and tablets (type A), 5W (5VDC @1A) power only, outlets with:
 - No load power consumption <0.3W
 - Meets EISA 2007 (Energy Independence and Security Act)
 - ErP step 2 compliant, FCC part 15, class B compliant, UL 60950-1 and CSA 22.2 approved
 - UL 60950-1 and CSA 22.2 approved, MTBF 1100Khrs min, MIL-HDBK-217°F (25°C)

- 4 1 RU, standard EIA 19 inch panel configuration.
- 5 Optional cable pass through grommet.
- 6 Sturdy 14 ga steel construction with integrated stiffener for added rigidity. Durable powder coat finish resists scratches. UL approved components.
- (5X) Data pass through ports, independently configurable with any standard Keystone connector type.





WARRANTY: 3 year parts and labor replacement warranty based on normal use and wear and tear.

\$425°°



For more information: (212) 390-1303 walter@stfconsoles.com